

ML110

4G Modem/Router

Description

The LEANOTEK ML110 is a **CAT1 “Economy Model”** will gives you a simple LTE connectivity solution for your devices, Plug a SIM card , Simply connect this modem directly to your router, switch or computer to provide an automatic 4G or 2G backup connection with download speeds of up to 10 Mbps. It has also an Ethernet WAN port so that you can plug in and share connection with all your Wi-Fi and wired devices. The LEANOTEK 4G Modem is also compact, convenient, and simple to setup.



Specifications

Hardware Specification	LTE Chipset : ASR, DDR:128 MB, Flash 32MB WiFi Chipset : Mediatek
LTE Standard	3GPP Release 9
Button	WPS, Reset
USIM	1.8V/3V 2FF
LTE Specification	Category: 1 (10Mbps Downlink, 5Mbps Uplink) Antenna: 5dBi Internal
Wi-Fi Specification	Rate: 2.4GHz (300Mbps) Antenna: 2.4GHz 4dBi Internal – 2x2 MIMO Frequency: 802.11b/g/n (2.412GHz-2.482GHz)
Physical Ports	1*ETH RJ45 LAN Port 10/100 Auto-Sensing, Auto-MDI/MDIX 1*SIM Card Holder
Number of Concurrent Users	32
IP Index – Dual Stack	IPV4/IPV6
Operation Mode	Router/NAT/Bridge
TR069	Support
Cell Lock	Support
L2/L3 Firewall	Support
NAT Mode	Support

ML110

4G Modem/Router

DHCP	Support
DMZ	Support
GRE Tunneling	Support
Multi APN	Support
IP Routing	Support
SSH/Telnet	Support
Port Forwarding	Support
PPTP, L2TP VPN client	Support
Web base Management - GUI	Support
Working Frequency	LTE-FDD: B1/B3/B5/B7/B8/B20 LTE-TDD: B38/B40/B41 GSM: 900/1800MHz
Working Environment	Operation temperature: -40°C to +85°C
Power	Input Universal Range 100~240V AC , Output : 12V/1.0A DC
Power Consumption	<12W
Case	ABS Material, Plastic case
Physical Features	180*130*45 mm